

In vitro fermentation parameters of brachiaria straw and starchy by-products

Parâmetros de fermentação in vitro de palha de braquiária e subprodutos amiláceos

Bruna Cardoso Braga^{1*}; Ricardo Augusto Mendonça Vieira²; Severino Delmar Junqueira Vilela³; Paulo Gustavo Macedo de Almeida Martins⁴; Raphael dos Santos Gomes⁵; Fernando de Paula Leonel⁶

Highlights

The starchy feedstuffs showed more intense fermentation in the first hours.
The fibrous feedstuffs fermentation occurred more slowly in the first hours.
The diets showed lower k1 values and higher k2 values when compared to corn silage.
The results confirm the possibility of using the wastes in ruminant feeding.

Abstract

Our objective was to characterize the degradation kinetics of fibrous and starchy agro-industrial wastes that can be used as feed for ruminants. Unprocessed *Brachiaria* straw hay (UBH), processed (briquetting) *Brachiaria* straw hay (PBH), a starchy by-product from potato processing (SBP), and cassava starch (CST) were evaluated. Two diets were formulated: one including UBH and CST (UBH-CST); and the other PBH and SBP (PBH-SBP). For the study of degradation kinetics, the *in vitro* cumulative gas production fermentation technique was used, in which the two-compartment Monomolecular-G3G1 model provided a more likely fit. The cumulative gas volumes produced were 23.2 (UBH), 29.6 (PBH), 39.1 (SBP), 36.6 (CST), 27.9 (UBH-CST), and 28.5 (PBH-SBP) mL per 0.1 g of dry matter. The starchy feedstuffs showed more intense fermentation in the first hours ($\hat{K}_1=1.050$ and 0.627 , for CST and SBP, respectively). This agile fermentation occurs because this is a soluble and/or rapidly degradable feedstuff that contains a very small amount of fibrous matter. As for the fibrous feedstuffs, UBH and PBH, fermentation occurred more slowly in the

¹ Student of the Master's Course of the Postgraduate Program in Animal Science, Universidade Federal dos Vales de Jequitinhonha e Mucuri, UFVJM, Diamantina, MG, Brazil. E-mail: braga.braga@discente.ufg.br

² Prof. Dr., Universidade Estadual do Norte Fluminense Darci Ribeiro, UENF, Campos dos Goytacazes, RJ, Brazil. E-mail: ramvieira@uenf.br

³ Prof. Dr., UFVJM, Diamantina, MG, Brazil. E-mail: sdjvillela@gmail.com

⁴ Researcher, UFVJM, Diamantina, MG, Brazil. E-mail: pgmartins@outlook.com

⁵ Prof. Dr., Instituto Federal de Educação, Ciência e Tecnologia de Rondônia, IFRO, Colorado do Oeste, RO, Brazil. E-mail: raphael.gomes@ifro.edu.br

⁶ Prof. Dr., Universidade Federal de São João del Rei, UFSJ, São João del Rei, MG, Brazil. E-mail: fernandoleonel@ufsj.edu.br

* Author for correspondence

first hours ($\hat{K}_1=0.212$ and 0.121 , for UBH and PBH, respectively), releasing less gas. Because fiber has a slowly degradable and insoluble part, the asymptotic phase takes longer to be reached. The diets, on the other hand, exhibited fermentation intermediate to those of the starchy and fibrous feedstuffs ($\hat{K}_1=0.141$ and 0.127 , for UBH-CST and PBH-SBP, respectively), what faithfully followed the gas production profile of their ingredients. Both diets showed lower k_1 values and higher k_2 values when compared to corn silage. The characterization of agro-industrial residues, using the *in vitro* cumulative gas production technique, confirms the real possibility of using the studied by-products in feeding ruminants.

Key words: Briquetting. Cassava starch. *In vitro* gas production. Potato starch. Straw processing.

Resumo

Nosso objetivo foi caracterizar a cinética de degradação de resíduos agroindustriais fibrosos e amiláceos que podem ser utilizados na alimentação de ruminantes. Foram avaliados feno de palha de braquiária não processado (UBH), feno de palha de braquiária processado (briquetagem) (PBH), um subproduto amiláceo do processamento de batata (SBP) e fécula de mandioca (CST). Duas dietas foram formuladas: uma incluindo UBH e CST (UBH-CST); e o outro PBH e SBP (PBH-SBP). Para o estudo da cinética de degradação, foi utilizada a técnica de fermentação de produção cumulativa de gás *in vitro*, na qual o modelo Monomolecular-G3G1 de dois compartimentos forneceu um ajuste mais provável. Os volumes cumulativos de gás produzidos foram 23,2 (UBH), 29,6 (PBH), 39,1 (SBP), 36,6 (CST), 27,9 (UBH-CST) e 28,5 (PBH-SBP) mL por 0,1 g de matéria seca. Os alimentos amiláceos apresentaram fermentação mais intensa nas primeiras horas ($\hat{K}_1=1,050$ e $0,627$, para CST e SBP, respectivamente). Essa fermentação ágil ocorre porque se trata de um alimento solúvel e/ou rapidamente degradável que contém uma quantidade muito pequena de matéria fibrosa. Já para os alimentos fibrosos, UBH e PBH, a fermentação ocorreu mais lentamente nas primeiras horas ($\hat{K}_1=0,212$ e $0,121$, para UBH e PBH, respectivamente), liberando menos gases. Como a fibra tem uma parte lentamente degradável e insolúvel, a fase assintótica demora mais para ser alcançada. Já as dietas apresentaram fermentação intermediária às dos alimentos amiláceos e fibrosos ($\hat{K}_1=0,141$ e $0,127$, para UBH-CST e PBH-SBP, respectivamente), o que acompanhou fielmente o perfil de produção de gases de seus ingredientes. Ambas as dietas apresentaram menores valores de k_1 e maiores valores de k_2 quando comparadas à silagem de milho. A caracterização dos resíduos agroindustriais, por meio da técnica de produção cumulativa de gases *in vitro*, confirma a real possibilidade de utilização dos subprodutos estudados na alimentação de ruminantes.

Palavras-chave: Briquetagem. Fécula de mandioca. Produção de gás *in vitro*. Fécula de batata. Processamento de palhada.

Introduction

The harvest of tropical forage seeds generates 2.88 million tons of straw annually (consisting of remaining leaves, stems, and inflorescences) (Catuchi et al., 2017). Using

this material in ruminant feeding is an obvious option; however, due to its low nutritional quality, this practice is only performed occasionally. The low density of straw is also a logistic problem in terms of transport and storage (Souza & Cardoso, 2003).

Straw can be processed, through the deconstruction of lignocellulose (Souza, 2001), to increase its digestibility and intake. To address the abovementioned issues, an industrial process denominated 'briquetting' can be employed, which consists of compressing raw material under high pressure, causing lignin to be liberated and bind the material into a firm briquette (Nikolaisen & Jensen, 2013). Considering that this material has the potential to be used in ruminant feeding, it is important to evaluate the kinetics of passage and ruminal degradation of this fiber.

The use of by-products in animal feeding could mitigate the issue of pollution in the agricultural industry (Pen et al., 2006), and, if not used, it presents a high cost of waste treatment (Nkosi & Meeske, 2010). Starchy by-products from the processing of cassava and potato can be an alternative in ruminant feeding, especially for the partial or complete substitution of corn, a costly diet ingredient (Marques et al., 2000; Silva et al., 2013).

World cassava production is more than 180 million tons annually. Although there are no absolute data regarding the total amount of waste produced from industrialization, it is known that around 10% of the total cassava used in the manufacture of flour is eliminated in the form of peel and around 3 to 5%, in the form of sweeping flour (Zeoula et al., 2002). Research on cassava and its by-products stands out due to the ease of its cultivation, in addition, there is the possibility of using its cultural residues (leaves and stems), and its industrial by-products (hull, flour and starch) in animal feed.

In potato processing and processing industries, approximately 35% of the potatoes produced are discarded, in addition to producing a large number of by-products. These residues can be used to feed ruminants as they have high starch content and minimize production costs. Furthermore, the possibility of using tubers unsuitable for human consumption eliminates an economic and environmental problem (Silva et al., 2013).

Knowledge of the feedstuffs used in diets is important to allow animals to express their maximum production potential (Senger et al., 2007). One of the methods to evaluate the degradability and kinetics of ruminal fermentation is the *in vitro* gas production approach, described by Theodorou et al. (1994). This technique has been used due to its satisfactory and rapid results, in addition to being a low-cost alternative compared with the *in vivo* method. Furthermore, the use of mathematical modeling based on the obtained results can generate a good estimate of the kinetic processes of degradation (Vieira et al., 2008).

The hypothesis regarding fibrous byproducts is that, in theory, briquetting processing can promote some destabilization of the material's lignocellulosic matrix, due to the increase in pressure and temperature during the industrial process. This possible destabilization could increase the transit kinetics and ruminal degradation of the fiber. Regarding starchy by-products, due to their high starch content, they have the potential to replace corn partially or completely in rations without compromising animal performance, which configures the other hypothesis to be studied in this work. Therefore, our objective was to characterize the fermentation kinetics,

using the *in vitro* cumulative gas production technique, of some agro-industrial wastes that can be used as feed for ruminants.

Material and Methods

The present experiment was reviewed and approved by the Animal Use Ethics Committee of the State University of Norte Fluminense (Protocolo 380 da CEUA/UENF).

Four feedstuffs were evaluated to determine degradation kinetics and diet composition: (1) unprocessed *Brachiaria* straw (UBH); (2) processed (briquetting) *Brachiaria* straw (PBH); (3) a starchy by-product from potato processing (SBP); and (4) cassava starch (CST). The unprocessed *Brachiaria* straw was obtained after the harvest of tropical forage seeds. The UBH was obtained by simply baling field straw. To obtain PBH, the straw was ground and then subjected to the briquetting process. The briquetting process consists of the continuous evolution of the material in metal tubes under pressure, which increases the temperature of the material. This process considerably increases the density of the material and transforms it into a pressed material called "briquettes", and known commercially as "briqfeno", which in turn, considerably reduces the space used for transport and storage.

Potato starch (SPB) was obtained from the residue of a factory producing the commercial product "potato straw" provided by the company Crokes located in São João del Rei, MG. This by-product is the starch that comes off the outer part of the tubers during washing, containing a small contamination with the skin. Finally, the CST by-product

used in the present study is residue from the manufacture of sweet flour, it is a waste product from a machine.

The starchy by-product, SBP, was obtained from the potato chip manufacture waste; this by-product is the starch that detaches from the external part of the tuber during the cleaning process, which is slightly contaminated with skin. Finally, the CST by-product used in the present study is residue from the manufacture of sweet flour, it is a waste product from a machine.

Two diets were formulated using the feedstuffs: one including UBH and CST (UBH-CST), containing 69.5% UBH, 28.0% CST, and 2.5% urea; and the other including PBH and SBP (PBH-SBP), containing 67.7% PBH, 29.5% SBP, and 2.8% urea. The energy and protein contents were standardized to a high enough level to meet the nutritional requirements of a cow with a body weight of 200 kg and with an average daily gain of 0.5 kg/d (Agricultural and Food Research Council [AFRC], 1993). Urea was used to balance the protein level.

Samples of the tested feedstuffs were weighed and dried in a forced-air oven at 55°C for 72 h. Then, the material was weighed again to obtain the partial dry matter (DM). Feedstuffs were ground in Wiley mills to pass through a 1-mm round-curved sieve (Theodorou et al., 1994). Total DM (method 976.03; Association of Official Analytical Chemists [AOAC], 1990), ash (method 942.05; AOAC, 1990), crude protein (method 987.04; AOAC, 1990), neutral detergent fiber (NDF; method AOAC 2002.04), acid detergent fiber (ADF), and lignin (method 973.18; AOAC 1977) in the diets and feedstuffs were determined (Table 1).

Table 1
Chemical composition of feedstuffs and diets

Item, g/kg dry matter	Feedstuff ¹				Diet ²	
	UBH	PBH	SBP	CST	UBH-CST	PBH-SBP
Dry matter	900.3	918.2	957.5	874.7	904.6	932.1
Crude protein	52.2	51.1	3.3	3.1	70.3	103.3
Neutral detergent fiber	760.5	736.6	40.8	n.a.	530.9	503.0
Acid detergent fiber	453.8	439.4	29.5	5.9	307.8	300.3
Lignin	63.9	35.2	n.a.	0.8	40.4	34.5
Mineral matter	44.8	54.5	4.3	3.8	36.3	53.9

¹ UBH = unprocessed Brachiaria straw hay; PBH = processed (through briquetting) Brachiaria straw hay; SBP = starch by-product of potato processing; CST = cassava starch.

² Two diets were formulated, one using UBH and CST (UBH-CST) and the other one with PBH and SBP feedstuffs (PBH-SBP).

n.a.: not available: undetectable due to very small amounts present in the feedstuff.

The cumulative gas production from fermentation was determined through in vitro anaerobic incubations, based on the methodology described by Malafaia et al. (1998). Rumen inoculum was made up of the combination of ruminal contents from three steers with permanent cannulas in the rumen, which were fed twice daily, at 08.00 hand at 16.00 h, for 15 days. The diet was formulated based on the metabolic weight of the cattle under maintenance (AFRC, 1993), it was composed of 35:65 (concentrate: roughage), the roughage offered was hay and the concentrate was made up of 86% ground corn; 11.5% soybean meal and 2.5% kg of urea.

The liquid and solid materials from the rumen inoculum were collected separately and stored in thermos flasks with a wide opening. The 2:1 liquid:solid ratio was used to prepare the inoculum, which was mixed in a blender for 60 hours under continuous CO₂ infusion. Then, the material was filtered through four layers of gauze. The filtered

inoculum was added to the culture medium at the ratio of 1:4 (Goering & Van Soest, 1970), respectively, and the mixture was kept at 39°C under continuous CO₂ sparging, until the moment when the mixture was transferred to flasks containing the samples.

A partially dried 0.5-g sample was incubated in amber-colored penicillin flasks (100 mL) and culture medium and rumen inoculum were added according to the procedures reported by Hall and Mertens (2008). Three flasks without sample (blank) were used for data correction. Twenty-one flasks with sample were distributed in the digestibility machine (triplicates of each sample and three flasks without sample, or blanks). The flasks were closed with rubber stoppers, sealed with aluminum seals, and kept in a water bath at 39°C.

Pressure and volume readings were taken at initial equilibrium (zero time) and at 1, 2, 3, 4, 6, 8, 10, 12, 16, 20, 24, 30, 36, 42, 48, 72, and 96 h after adding the rumen

inoculum. The gas pressures generated from the onset of fermentation were recorded by manometric readings (0-7 psi manometer, 0.05-psi increments), as well as the volumes displaced within a graduated pipette (0-25 mL, 0.1-mL increments) by the pressurized gas diverted into the pipette using a three-way valve. The pressure and cumulative volume of rumen fermentation gases were

$$V_t = Vf_1 \times (1 - \exp(-k_1 t)) + Vf_2 \times \left(1 - \left(\delta^N \exp(-k_2 t) + \exp(-\lambda t) \sum_{i=1}^{N-1} \frac{(1-\delta^{N-i})(\lambda t)^i}{i!} \right) \right) + e_t \quad (\text{eq. 1})$$

adopting $V_t \sim \text{Normal}(\mu_{V_t}, \sigma_{V_t}^2)$, that is, we assumed that variable V_t follows a normal distribution with average function μ_{V_t} . This function (Eq. 1) represents the two-compartment model composed of the monomolecular and GNG1 models (Vieira et al., 2008), in which Vf_1 and Vf_2 (mL) are the asymptotic volumes of gases produced by the rapidly and slowly degradable fractions; k_1 is the fractional rate (1/h) of fermentation of carbohydrates of the rapidly degradable fraction; k_2 is the rate (1/h) of fermentation of carbohydrates of the slowly degradable fraction of the feedstuff DM; N is a positive integer that represents the order of time dependence; and λ (1/h) is the asymptotic rate of preparation of the insoluble and slowly degradable substrate for digestion.

When fitting the accumulated gas production profiles, the data were grouped using the grouped Data function of the nlme package do pacote nlme do software R (R version 4.0.0, R Foundation for Statistical Computing, Vienna, Austria), considering equations 2 and 3:

$$V \sim \text{Time} | \text{rep} / \text{flask} \quad (\text{eq. 2})$$

$$V \sim \text{Time} | \text{flask} \quad (\text{eq. 3})$$

determined by adding the corrected readings at the times performed. The volumes of gases read were standardized in mL per 0.1 g of DM of incubated sample.

Equation 1 represents the general structure attributed to the nonlinear model used to quantitatively interpret the cumulative gas production profiles:

in which V = cumulative volume of gas produced; Time = times when volume readings are taken in each flask; rep = replicates in each treatment; and flask = effect of the experimental unit.

The conventional assumption of homoscedasticity was evaluated using the nlme function from the nlme package of R software (R Foundation for Statistical Computing, Vienna, Austria). The variance was modeled according to equations 4 and 5: (Pinheiro & Bates, 2000):

$$\sigma_{V_t}^2 = \sigma^2; \quad (\text{eq. 4})$$

$$\sigma_{V_t}^2 = \sigma^2 (V_t)^{2\psi}. \quad (\text{eq. 5})$$

where σ^2 is the homogeneous residual variance, as shown by equation (4). Equation 5 represents the residual variance ($\sigma_t^2 = \sigma^2$) scaled by the power (ψ) as a function of the expected mean, V_t . In the adjustment of the accumulated gas pressure profiles, the general correlation between the repeated measurements over time for each flask was added using the continuous autoregressive correlation (AR1) of the nlme package of R (Pinheiro & Bates, 2000).

The models were fitted to the cumulative gas production profiles using the nlme package of R (Pinheiro & Bates, 2000). In all cases, the models were fitted considering data groupings and the model combinations for interpreting the gas profiles, and the fits were compared using the Akaike information criterion (Akaike, 1974; Sugiura, 1978; Burnham & Anderson, 2004). The Akaike criterion tests which function, or functions best represent the data distribution (Akaike,

1974), that is, it chooses the model that causes the least loss of information (Burnham & Anderson, 2004). Rejection or non-rejection of the null hypothesis, used in the likelihood ratio test to test normality against another possible distribution, should be avoided. The models were fitted separately for diets, starchy and fibrous feedstuffs (Table 2). The predictive parameters were compared using the 95% confidence interval.

Table 2
Model that presented the best fit to the cumulative gas production profiles

Feedstuffs ¹	N ²	Variance type	Correlation ³	Degree of freedom	AICc ⁴
CST and SBP	3	Exponential	Yes	12	119.8
UBH and PBH	3	Homogeneous	Yes	13	-92.1
PBH-SBP and UBH-CST	3	Homogeneous	Yes	13	134.0

¹UBH = unprocessed Brachiaria straw hay; PBH = processed (through briquetting) Brachiaria straw hay; SBP = starch by-product of potato processing; CST = cassava starch; UBH-CST= diet were formulated using UBH and CST; PBH-SBP = diet were formulated using PBH and SBP

²N is a positive integer that represents the order of time dependence

³Correlation auto regressive (AR1 in nlme package)

⁴Akaike information criterion.

Results and Discussion

According to Akaike's information criterion, corrected for sample size, in establishing the order of time dependence (N) for equation 1 for the two diets and their feed ingredients, we observed that increments in the value of N up to 3 provided a more likely fit of the model (Monomolecular-G3G1) to the cumulative gas production data. In choosing the best grouping structure to be used in the construction of the grouped Data function of the nlme package of R software, we observed that equation 2 (which includes

the replicate effect) provided more likely fits to the profiles of cumulative gas production. The model fitted for the diets and starchy and fibrous feedstuffs was the Monomolecular-G3G1 model, in which increments in the value of N up to 3 provided a more likely fit of the model to the cumulative gas production data. The inclusion of the correlation function and the variance function provided considerable improvement in the fitting of the model to the profiles. The parameters estimated using the Monomolecular-G3G1 model are analogous to what the graphs illustrate (Figures 1 and 2).

In vitro degradability by gas production follows a sigmoid curve and can be divided into three phases, according to Cheng et al. (1980): 1) the slow phase, without gas production (initial phase); 2) the fast gas production phase (exponential phase); and 3) the phase in which the gas production rate decreases, reaching zero (asymptotic phase). The gas released from feedstuffs inoculated

with rumen fluids reflects microbial activity and can provide information on degradability and fermentation kinetics. The curves generated by the two diets followed the same pattern, as did the respective curves for the feedstuffs. The difference in exponential and asymptotic phases between the curves of starchy and fibrous feedstuffs was noteworthy (Figure 1).




Figure 1. Sigmoid curves of the accumulation of gas volume produced during the 96 hours of incubation.

The curves of the starchy and fibrous feedstuffs were different during the exponential phase because of the more intense fermentation in starchy feedstuffs in the first hours. The asymptotic phase of the starchy feedstuffs was reached quickly, demonstrating the accelerated fermentation rate of the starch from the feedstuffs evaluated here. This agile fermentation occurs because this is a soluble and/or rapidly degradable feedstuff that contains a very small amount

of fibrous matter, as confirmed by chemical analysis (Table 1).

The sigmoid curves of the fibrous feedstuffs, UBH and PBH, show that in the first hours, fermentation occurred more slowly, releasing less gas, which is due to the greater amounts of NDF, ADF, and lignin present in this material (Table 1). Because fiber has a slowly degradable and insoluble part, the asymptotic phase takes longer to

be reached, when compared with starchy ingredients. The curves generated by the two diets followed the same pattern as the food curves and were intermediate between the curves of starchy and fibrous foods, that is, their gas production values were lower than those of starchy foods and higher than those of fibrous foods.

Cumulative gas production data allow us to compare the different diets regarding their final gas production and the degradation rates of the soluble and fibrous fractions. The accumulated gas production values were

39.1, 36.6, 29.6, 23.2, 27.9 and 28.5 for SBP, CST, UBH, PBH, UBH-CST and PBH-SBP, respectively. The volume of cumulative gas produced from SBP was greater than that produced from CST. Initially, CST produced a greater amount of gas, that is, greater initial fermentation. Gas production by SBP, from the twelfth reading (24 h after incubation), exceeded that of CST and remained greater until the last reading (Figure 2), producing a cumulative gas volume of 39.1 mL/0.1g DM, which is greater than the 36.6 mL/0.1g DM produced by CST.




Figure 2. Gas production (mL per 0.1 g dry matter per hour) during the 96 hours of incubation of fibrous (UBH and PBH) and starch (SBP and CST) feedstuffs, and diets (UBH-CST and PBH-SBP)¹. ¹UBH = unprocessed Brachiaria straw hay; PBH = processed (through briquetting) Brachiaria straw hay; SBP = starch by-product of potato processing; CST = cassava starch (CST). Two diets were formulated, one using UBH and CST (UBH-CST) and the other one with PBH and SBP feedstuffs (PBH-SBP).

The gas production profiles of UBH and PBH were similar; however, in the last readings, the lines representing gas production by PBH were above those of UBH (Figure 2), resulting in cumulative gas volumes of 29.6 and 23.2 mL/0.1 g DM, respectively. The cumulative volume of gas produced by the PBH-SBP diet (28.5) was greater than that produced by the UBH-CST diet (27.9 mL/0.1g DM), similarly to what happened with the respective starchy and fiber feedstuffs in each diet (Fig. 2).

Cabral et al. (2002) used the two-compartmental logistic model to estimate the kinetics of cumulative gas production and found final gas volumes of 20.03, 23.35, 25.77, 26.95 and 28.47 for corn silages with 0, 15, 30, 45 and 60% grains. According to bromatological analyses, the diets in studies present a chemical composition (crude protein, neutral detergent fiber, acid detergent fiber, lignin and mineral matter) between silage with inclusion of 0 to 30% of grains, but the gas production of diets was similar to silage with inclusion of 60% grains, which had the best nutritional value according to the estimated parameters. This was probably due to the greater effective degradability of starch from tubers compared to starch from cereals, especially corn. The greater degradability is due to the lack of pericarp, horny and peripheral endosperm, protein matrix and possibly due to a lower proportion

of amylose and lipids in the starch granules, which reduces the amount of hydrogen bonds in the starch molecule and increases the capacity expansion of tuber starch in an aqueous medium (Zeoula & Caldas, 2001; Rangel et al., 2008).

According to the monomolecular-G3G1 model (Table 2), a greater rate of degradation of the soluble fraction (k_1) in any diet or feedstuff means greater degradation of the soluble or rapidly degradable fraction. The second rate (k_2) allows differentiating the diets in terms of the degradation of the slowly degradable fraction, proving to be an important measure in the selection of the diets with the highest-quality fibrous fraction. Table 3 presents the estimated values for Vf_1 , Vf_2 , K_1 , K_2 e λ starchy and fibrous foods and their respective diets. Based on the degradation rates, k_1 and k_2 , and their respective standard errors, the diets showed similar fermentation ($k_1=0.127$ and $k_2=0.040$ for PBH-SBP and $k_1=0.141$ and $k_2=0.037$ for UBH-CST). As for the fibrous feedstuffs, UBH exhibited a greater k_1 than PBH, whereas k_2 was greater in PBH ($k_1=0.212$ and $k_2=0.031$ for UBH and $k_1=0.121$ and $k_2=0.034$ for PBH). Between the starchy feedstuffs, CST showed greater values than SBP for both rates ($k_1=1.050$ and $k_2=0.157$ for CST and $k_1=0.627$ and $k_2=0.091$ for SBP).

Table 3

Estimated parameters (followed by their respective standard deviations) of the best models to diets and feedstuffs utilized in their composition, with variance and correlation values (followed by the lower and upper limits of the confidence interval)

Diet/feedstuff ¹	Parameter ² (standard error)					Variance and correlation (CI 95%)
	$\hat{V}f_1$	\hat{K}_1	$\hat{V}f_2$	\hat{K}_2	$\hat{\lambda}$	
UBH-CST	10.3 (2.37)	0.141 (0.0392)	17.6 (2.29)	0.037 (0.0050)	1.090 (0.3036)	$\hat{\sigma} = 0.272$ (0.221; 0.335) $\hat{\phi} = 0.569$ (0.484; 0.650)
PBH-SBP	11.7 (2.01)	0.127 (0.0402)	16.8 (2.17)	0.040 (0.0031)	0.736 (0.2706)	
UBH	7.2 (1.43)	0.212 (0.0555)	16.0 (1.42)	0.031 (0.0011)	0.411 (0.0869)	$\hat{\sigma} = 0.115$ (0.094; 0.140) $\hat{\phi} = 0.429$ (0.244; 0.637)
PBH	13.2 (1.05)	0.121 (0.0132)	16.4 (1.10)	0.034 (0.0018)	0.219 (0.0403)	
CST	2.9 (0.41)	1.050 (0.3670)	33.7 (0.58)	0.157 (0.0062)	0.510 (0.0429)	$\hat{\sigma} = 0.347$ (0.226; 0.534) $\psi = 0.02$ (0.006; 0.0340) $\hat{\phi} = 0.564$ (0.357; 0.750)
SBP	3.6 (0.74)	0.627 (0.2471)	35.5 (0.89)	0.091 (0.0070)	0.555 (0.0551)	

¹ UBH = unprocessed Brachiaria straw hay; PBH = processed (through briquetting) Brachiaria straw hay; SBP = starch by-product of potato processing; CST = cassava starch (CST). Two diets were formulated, one using UBH and CST (UBH-CST) and the other one with PBH and SBP feedstuffs (PBH-SBP).

² Vf_1 = asymptotic volumes of gases produced by the rapidly degradable fraction (mL); Vf_2 = asymptotic volumes of gases produced by the slowly degradable fraction (mL); K_1 = fractional rate (1/h) of fermentation of carbohydrates of the rapidly degradable fraction; K_2 = rate (1/h) of fermentation of carbohydrates of the slowly degradable fraction; and λ = asymptotic rate (1/h) of preparation of the insoluble and slowly degradable substrate for digestion.

The lower fermentation of fibrous foods in the first hours of incubation is demonstrated by the lower fermentation rates of the rapidly degradable fraction (K_1), with values of 0.212 and 0.121 for UBH and PBH, respectively. Because fiber has a slowly degradable and insoluble part, the asymptotic phase takes longer to be reached, when compared with starchy ingredients, where K_1 were 1.050 and 0.627 for CST and SBP, respectively (Table 3). Although UBH exhibited greater k_1 , in the last readings, gas production from PBH was greater than that of UBH. According to the G3G1-model, higher k_2 represents diets with a higher quality fibrous fraction. For this reason, the accumulated gas production of PBH was

greater than that of UBH. Further research is needed on the processing of Brachiaria straw by briquetting; however, the results suggest that processing had a positive effect, since it increased the cumulative volume of gas produced, indicating greater fermentation of this straw compared with unprocessed straw.

Malafaia et al. (1999), estimating kinetic parameters of dry matter degradation of some tropical forages using the gas production technique, found higher values for the volume of gas produced, as well as higher degradation rates for brachiaria grass (*Brachiaria decumbens*), both for slowly degradable and rapidly degradable fractions. The lower degradation rates of the brachiaria

straw studied here are probably since it is a residue coming from a more mature material (90% DM) (Table 1) when compared to the brachiaria grass used in the study above (28.9 % DM).

Regarding starchy foods, a possible explanation for the lower degradation rate of the slowly degradable fraction (k₂) of SBP is the larger amount of fiber present in this feedstuff when compared with CST. The greater amount of fiber present in SBP compared with CST is a consequence of the greater quantity of peels present in this by-product resulting from the industrial process. The by-product used to re-treat cassava starch (CST) is a residue from the manufacture of sweet tapioca flour, a machine waste product. Because it is a purely starchy product, the NDF of CST was not detected in the chemical analyses (Table 1).

The gas production profile of the diets faithfully followed the gas production profile of their ingredients (Figure 2). Both diets evaluated in the present study exhibited similar degradation rates. When compared to corn silage, they showed lower k₁ values. Conversely, the k₂ values of the tested diets (0.040 and 0.037) were greater than those of corn silage (Processi et al., 2016). Bendia et al. (2021) evaluated the nutritional potential of corn hybrids using the in vitro gas production technique and the values they estimated are comparable to those found in this study for diets. The k₁ values, according to the confidence interval presented in the study, were similar between corn (G₁= 0.140; G₂=0.141 and G₃=0.160) and the diets studied here (UBH-CST=0.141 and PBH-SBP = 0.127). The k₂ values of the diets were higher (UBH-CST=0.037 and PBH-SBP = 0.040) than those of corn (G₁= 0.024; G₂=0.021 and G₃=0.026).

Conclusion

The characterization of agro-industrial residues, using the in vitro cumulative gas production technique, confirms the real possibility of using the studied by-products in feeding ruminants.

References

- Agricultural and Food Research Council AFRC (1993). *Energy and protein requirements of ruminants*. CAB International.
- Akaike, H. (1974). A new look at the statistical model identification. *IEEE Transactions on Automatic Control*, 19(6), 716-723. doi: 10.1109/tac.1974.1100705
- Association of Official Analytical Chemists (1990). *Official methods of analysis* (15th ed.). AOAC International.
- Association of Official Analytical Chemists AOAC (1977). Official Method 973.18, Fiber (Acid Detergent) and Lignin in Animal Feed, in: *Official Methods of Analysis of AOAC International*, 16th edition (1997), Chapter 4, pp. 28-29, AOAC International, Arlington, VA.
- Bendia, L. C. R., Oliveira, J. G. de., Azevedo, F. H. V., Nogueira, M. A. dos R., Silva, L. V. da, Aniceto, E. S., Sant'Anna, D. F. D., Crevelari, J. A., Pereira, M. G., & Vieira, R. A. M. (2021). A two-location trial for selecting corn silage hybrids for the humid tropic: forage and grain yields and in vitro fermentation characteristics. *Revista Brasileira de Zootecnia*, 50, e20200110. doi: 10.37496/rbz5020200110
- Burnham, K. P., & Anderson, D. R. (2004). Multimodel inference: understanding AIC

- and BIC in model selection. *Sociological Methods & Research*, 33(2), 261-304. doi: 10.1177/0049124104268644
- Cabral, L. S., Valadares, S. C., F^o., Detmann, E., Zervoudakis, J. T., Pereira, O. G., Veloso, R. G., & Pereira, E. S. (2002). Cinética ruminal das frações de carboidratos, produção de gás, digestibilidade in vitro da matéria seca e NDT estimado da silagem de milho com diferentes proporções de grãos. *Revista Brasileira de Zootecnia*, 31(6), 2332-2339. doi: 10.1590/S1516-35982002000900023
- Catuchi, T. A., Soratto, R. P., Francisquini, A., Jr., Aranda, E. A., Guidorizzi, F. V. C., & Tiritan, C. S. (2017). Nitrogen management, nitrogen use efficiency, and seed yield and quality of creeping signalgrass. *Crop Science*, 57(5), 2865-2874. doi: 10.2135/cropsci2017.02.0096
- Cheng, K. J., Fay, J. P., Howarth, R. E., & Costerton, J. W. (1980). Sequence of events in the digestion of fresh legume leaves by rumen bacteria. *Applied Environment Microbiology*, 40(3), 613-625. doi: 10.1128/AEM.40.3.613-625
- Goering, H. K., & Van Soest, P. J. (1970). *Forage fiber analysis (apparatus reagents, procedures and some applications)*. Agriculture Handbook. United States Department of Agriculture.
- Hall, M. B., & Mertens, D. R. (2008). In vitro fermentation vessel type and method alter fiber digestibility estimates. *Journal of Dairy Science*, 91(1), 301-307. doi: 10.3168/jds.2006-689
- Malafaia, P. A. M., Valadares, S. C., F^o., Vieira, R. A. M., Coelho da Silva, J. F., & Pereira, J. C. (1998). Cinética ruminal de alguns alimentos investigada por técnicas gravimétricas e metabólicas. *Revista Brasileira de Zootecnia*, 27(2), 370-380.
- Malafaia, P. A. M., Valadares, S. C., F^o., & Vieira, R. A. M. (1999). Kinetic parameters of ruminal degradation estimated with a non-automated system to measure gas production. *Livestock Production Science*, 58(1), 65-73. doi: 10.1016/S0301-6226(98)00183-3
- Marques, J. A., Prado, I. N., Zeoula, L. M., Alcalde, C. R., & Nascimento, W. G. (2000). Avaliação da mandioca e seus resíduos industriais em substituição ao milho no desempenho de novilhas confinadas. *Revista Brasileira de Zootecnia*, 29(5), 1528-1536. doi: 10.1590/S1516-35982000000500035
- Nikolaisen, L. S., & Jensen, P. D. (2013). 3 - Biomass feedstocks: categorisation and preparation for combustion and gasification. In L. Rosendahl (Ed.), *Biomass combustion science, technology and engineering* (pp. 36-57). Cambridge, UK.
- Nkosi, B. D., & Meeske, R. (2010). Effects of whey and molasses as silage additives on potato hash silage quality and growth performance of lambs. *South African Journal of Animal Science*, 40(3), 229-237. doi: 10.4314/sajas.v40i3.7
- Pen, B., Iwama, T., Ooi, M., Saitoh, T., Kida, K., Iketaki, T., Takahashi, J., & Hidari, H. (2006). Effect of potato by-products based silage on rumen fermentation, methane production and nitrogen utilization in Holstein steers. *Asian-Australasian Journal of Animal Science*, 19(9), 1283-1290. doi: 10.5713/ajas.2006.1283

- Pinheiro, J. C., & Bates, D. M. (2000). *Mixed-effects models in S and S-PLUS*. Springer-Verlag Inc.
- Processi, E. F., Fontes, C. A. A., Vieira, R. A. M., Bendia, L. C. R., Rocha, T. C., & Fernandes, A. M. (2016). Degradability and kinetics of fibrous particles in cattle fed diets based on corn silage and concentrates with or without addition of lipids. *Revista Brasileira de Zootecnia*, 45(12), 773-780. doi: 10.1590/S1806-92902016001200007
- Rangel, A. H. N., Leonel, F. P., Braga, A. P., Pinheiro, M. J. P., & Lima, D. M., Jr. (2008). Utilização da mandioca na alimentação de ruminantes. *Revista Verde*, 3, 1-12.
- Senger, C. C. D., Mühlbach, P. R. F., Sanchez, L. M. B., Kozloski, G. V., Kist, G. P., Lima, L. D., & Perez, D., Netto. (2007). Comparação entre os métodos químicos, in situ e in vivo para estimativa do valor nutritivo de silagens de milho. *Ciência Rural*, 37(3), 835-840. doi: 10.1590/S0103-84782007000300036
- Silva, J. S., Borges, A. L. C. C., Silva, R. R., Duque, A. C. A., Souza, A. S., Ferreira, A. L., & Borges, I. (2013). Utilização de batata inglesa na dieta de ruminantes. *PUBVET*, 7(7), 549-618. doi: 10.22256/pubvet.v7n7.1523
- Souza, F. H. D. (2001). *Produção de sementes de gramíneas forrageiras tropicais*. EMBRAPA Pecuária Sudeste. (Documento, 30).
- Souza, F. H. D., & Cardoso, E. G. (2003). *Alternativa para o descarte de palhada resultante da produção de sementes de capim*. (Comunicado Técnico, 39). EMBRAPA Pecuária Sudeste.
- Sugiura, N. (1978). Further analysis of the data by Akaike's information criterion and the finite corrections. *Communications in Statistics. Theory and Methods*, 7(1), 13-26. doi: 10.1080/03610927808827599
- Theodorou, M. K., Williams, B. A., Dhanoa, M. S., McAllan, A. B., & France, J. (1994). A simple gas production method using a pressure transducer to determine the fermentation kinetics of ruminant feeds. *Animal Feed Science and Technology*, 48(3-4), 185-197. doi: 10.1016/0377-8401(94)90171-6
- Vieira, R. A. M., Tedeschi, L. O., & Cannas, A. (2008). A generalized compartmental model to estimate the fibre mass in the ruminoreticulum: 1. Estimating parameters of digestion. *Journal of Theoretical Biology*, 255(4), 345-356. doi: 10.1016/j.jtbi.2008.08.014
- Zeoula, L. M., & Caldas, S. F., Netto. (2001). Recentes avanços em amido na nutrição de vacas leiteiras. In: Simpósio Internacional em Bovinocultura de Leite, 2., 2001, Lavras. *Anais...* Lavras: Universidade Federal de Lavras, 2001. p. 249-284.
- Zeoula, L. M., Caldas, S. F., Netto, Branco, A. F., Prado, I. N. do, Dalponte, A. O., Kassies, M., & Fregadolli, F. L. (2002). Mandioca e resíduos das farinheiras na alimentação de ruminantes: pH, concentração de N-NH₃ e eficiência microbiana. *Revista Brasileira de Zootecnia*, 31(3), 1582-1593. doi: 10.1590/S151635982002000600030